

6110 B11 SFR Superfast

Fast, soft, semi-lightweight putty

Super fast and easy to sand semilightweight polyester putty.

silco[®]

- / Dries up to 50% faster than conventional putties
- / Specific weight 1.45 kg/L
- / Ready to sand in 8 minutes from application
- / Excellent sanding, beginning with P150
- / Very easy to spread



6110 B11 SFR Superfast

Fast, soft, semi-lightweight putty

Drying time*

Dry to sand 20°C / 68 F	8–10 min
Potlife 20°C / 68 F	3–4 min

*Indicative times subject to amount of hardener/application/environment.

How to use?

Treated surface must be clean, dry, rust-free and grease-free. Optimal adhesion can be achieved on well abraded surface. For aluminium and galvanized steel, use matting pad+matting paste to improve adhesion. Mix the putty and hardener thoroughly until the colour is even. Use filler knife, plastic or rubber spatula for the application. Do not overdose! Excessive quantity of hardener can cause colour change on the topcoat and shorten the potlife. Hardener quantities below 2% can result in prolonged drying time.

For further and updated information please refer to the TDS published on www.silco.si.

Packaging

Putty & Hardener

Prod. Nr.	Content	Color
6110-1	1 L	White
6110-1,5	1.5 L	White
6110-3	3 L	White
BPO Hardener 2–3 %	50 g, 60 g, 70 g	Red paste

Product info

Super fast and easy to sand, semi-lightweight polyester putty. Our putty is sandable in 8 minutes (20°C) without paper clogging. Sanding easy and fast, leading to less paper usage. It dries up to 50% faster than conventional putties.